

**Amendments to the Claims:**

This listing of claims will replace all prior versions, and listings, of claims in the application:

**Listing of Claims:**

1                   1.       (Previously presented) A control method for a storage system which  
2 comprises a plurality of information processing units, a storage device provided with a plurality  
3 of logical volumes, and a user interface, said control method comprising:  
4                   performing a first process in which when a data write request to a first logical  
5 volume is sent from the information processing unit to the storage device the storage device  
6 stores data in the first logical volume and also stores the data in a second logical volume;  
7                   performing a second process in which the storage device suspends the first  
8 process; and  
9                   shifting from the second process to the first process to perform the first process;  
10                  when shifting from the second process to the first process to perform the first  
11 process, inquiring an information processing unit which can access the second logical volume, of  
12 whether said information processing unit mounts the second logical volume or not;  
13                   deciding whether said information processing unit mounts the second logical  
14 volume or not; and  
15                   when the information processing unit mounts the second logical volume,  
16 outputting that effect from said user interface before shifting to the first process.

1                   2.       (Previously presented) A control method for a storage system which  
2 comprises a plurality of information processing units, a storage device provided with a plurality  
3 of logical volumes, and a user interface, said control method comprising:  
4                   performing a process in which when a data write request to a first logical volume  
5 is sent from the information processing unit to the storage device the storage device stores data  
6 in the first logical volume and also stores the data in a second logical volume;

7                   when the control is to be newly initiated between the first logical volume and the  
8   second logical volume, inquiring an information processing unit which can access the second  
9   logical volume, of whether said information processing unit mounts the second logical volume or  
10   not;

11                  deciding whether the information processing unit mounts the second logical  
12   volume or not; and

13                  when the information processing unit mounts the second logical volume,  
14   outputting that effect from said user interface without being newly initiated between the first  
15   logical volume and the second logical volume.

1                  3.     (Previously presented) A control method for a storage system which  
2   comprises a plurality of information processing units, a storage device provided with a plurality  
3   of logical volumes, and a managing computer, and, said control method comprising:

4                  performing a first process in which when a data write request to a first logical  
5   volume is sent from the information processing unit to the storage device the storage device  
6   stores data in the first logical volume and also stores the data in a second logical volume;

7                  performing a second process in which the storage device suspends the first  
8   process;

9                  shifting from the second process to the first process to perform the first process;

10                 when shifting from the second process to the first process to perform the first  
11   process, inquiring an information processing unit which can access the second logical volume of  
12   whether the information processing unit mounts the second logical volume or not;

13                 deciding whether the information processing unit mounts the second logical  
14   volume or not; and

15                 when the information processing unit mounts the second logical volume,  
16   outputting that effect from a user interface of the managing computer before performing the first  
17   process.

1                   4.       (Previously presented) A storage system control method according to  
2 claim 1, wherein when the information processing unit does not mount the second logical  
3 volume the storage device shifts from the second process to the first process to perform the first  
4 process.

1                   5.       (Previously presented): A control method for a storage system which  
2 comprises a plurality of information processing units, a first storage device provided with a first  
3 logical volume in a first site, a second storage device provided with a second logical volume in a  
4 second site, said method comprising:

5                   performing a first process in which when a data write request to the first logical  
6 volume is sent from the information processing unit to the first storage device the first storage  
7 device stores data in the first logical volume, the first storage device sends the data to the second  
8 storage device, and the second storage device which receives the data stores the data in the  
9 second logical volume;

10                  performing a second process in which the second storage device suspends the first  
11 process;

12                  the second storage device shifting from the second process to the first process to  
13 perform the first process;

14                  when shifting from the second process to the first process to perform the first  
15 process, inquiring an information processing unit which can access the second logical volume of  
16 whether the information processing unit mounts the second logical volume or not;

17                  deciding whether the information processing unit mounts the second logical  
18 volume or not; and

19                  when the information processing unit mounts the second logical volume,  
20 outputting that effect from a user interface before shifting to the first process.

1                   6.       (Previously presented) A storage system control method according to  
2 claim 5, wherein when the information processing unit does not mount the second logical  
3 volume the second storage device shifts from the second process to the first process to perform  
4 the first process.

1                   7.       (Previously presented) A storage system connectable to a plurality of  
2 information processing units, a storage device provided with a plurality of logical volumes, and a  
3 user interface, said storage system comprising:

4                         means for performing a first process in which when a data write request to a first  
5 logical volume is sent from the information processing unit to the storage device the storage  
6 device stores data in the first logical volume and also stores the data in a second logical volume;

7                         means for performing a second process in which the storage device suspends the  
8 first process;

9                         means for shifting from the second process to the first process to perform the first  
10 process;

11                        means for inquiring an information processing unit which can access the second  
12 logical volume of whether the information processing unit mounts the second logical volume or  
13 not when shifting from the second process to the first process to perform the first process;

14                        means for deciding whether the information processing unit mounts the second  
15 logical volume or not; and

16                        means for, when the information processing unit mounts the second logical  
17 volume, outputting that effect from said user interface before shifting to the first process.

1                   8.       (Previously presented) A managing computer connectable to a storage  
2 system which comprises a plurality of information processing units and a storage device  
3 provided with a plurality of logical volumes, said managing computer comprising:

4                         means for shifting from a second process to a first process to perform the first  
5 process;

6 means for inquiring an information processing unit which can access a second  
7 logical volume of whether the information processing unit mounts the second logical volume or  
8 not when shifting from the second process to the first process to perform the first process,  
9 wherein said first process is that the storage device stores data in a first logical volume and also  
10 stores the data in the second logical volume, wherein said second process is that the storage  
11 device suspends the first process; and

12 means for, when the information processing unit mounts the second logical  
13 volume, outputting that effect from said user interface before shifting to the first process.

9. (canceled)

1 10. (Previously presented) A computer-readable storage medium having a  
2 program for a managing computer in a storage system comprising a plurality of information  
3 processing units and a storage device provided with a plurality of logical volumes, said program  
4 comprising:

5 code for performing a first process in which when a data write request to a first  
6 logical volume is sent from the information processing unit to the storage device the storage  
7 device stores data in the first logical volume and also stores the data in a second logical volume,

8 code for performing a second process in which the storage device suspends the  
9 first process;

10 code for shifting from the second process to the first process to perform the first  
11 process,

12 code for inquiring an information processing unit which can access the second  
13 logical volume of whether the information processing unit mounts the second logical volume or  
14 not when shifting from the second process to the first process to perform the first process,

15 code for deciding whether the information processing unit mounts the second  
16 logical volume or not, and

17                   code for, when the information processing unit mounts the second logical volume,  
18   outputting that effect from a user interface of the managing computer before shifting to the first  
19   process.